

AWNMAX[®]

antiwicking scrim, hard acrylic topcoat.



1153 MED. BLUE



1150 DK. BLUE



8102 SULTAN BLUE



6111 ROYAL BLUE



8101 NAVY BLUE



1162 CREAM



1170 IVORY



4144 TEAL



1142 DK. GREEN



6107 FOREST GREEN



*1160 COOL WHITE



1171 TAN



8103 SAND



1132 YELLOW



1181 GOLD



6102 GREY



3180 BLACK



6105 CORPORATE RED



8104 CARDINAL RED



6103 BURGUNDY

- Proven durability and performance with 20 years trouble-free track record
- Unparalleled translucent quality, not just brighter but better quality illumination
- Flame retardant meets C.S.F.M., NFPA 701, CAN/ULCS109M
- Exceedingly strong knitted polyester scrim
- Unrivalled dye lot consistency - production after production color consistency
- Patented hard acrylic topcoat provides superior cleanability, resists marking and bruising
- Super smooth top surface stays clean longer, easier to clean
- Accepts 3M Scotcheal translucent films for graphic decoration
- Weldable
- 10 year warranty

	STANDARD	METRIC (W/F)		ENGLISH (W/F)	
Width X Length	ASTM D-751	203cm X 29m		80 inch X 32 yds	
Weight	ASTM D-751	640	g / m ²	19	oz / yd ²
Thickness	ASTM D-751	0.52	mm	20	mil
Tensile Strength (Strip)	ASTM D-751	1,870 / 1,530	N/5cm	214 / 175	lbs / inch
Breaking Elongation	ASTM D-751	25 / 26	%	25 / 26	%
Tear Strength (Trapezoid)	ASTM D-751	215 / 170	N	48 / 38	lbs

The above mentioned data are average measurement value.



Manufactured by

HIRAOKA & CO., LTD.
 Tokyo, Japan
hira1902@tarpo-hiraoka.com
www.tarpo-hiraoka.com