



---

## SuperScreen 254

## Technical Data

---

Hiraoka SuperScreen 254 is a high strength PVC coated polyester mesh. It has excellent dimensional stability and very high UV resistance.

SuperScreen meshes are used in a range of applications from tents to sight-screens to truck tarps.

SuperScreen 254 is ideally suited for use in high strength applications such as insect screens for tents and camper trailers.

<b>Base Fabric</b>	<b>Polyester</b>
<b>Coating</b>	<b>PVC</b>
<b>Weight (g/m<sup>2</sup>)</b>	<b>130</b>
<b>Tensile Strength (N/50mm)</b>	<b>848 x 848</b>
<b>Elongation (%)</b>	<b>15 x 18</b>
<b>Tear Strength (N)</b>	<b>102 x 102</b>
<b>Fungal Resistance</b>	<b>Treated</b>
<b>Fire Retardant</b>	<b>Yes</b>
<b>Roll Size (m)</b>	<b>1.89 x 50</b>
<b>Colour</b>	<b>Grey, Black</b>
<b>Shade Factor (% approx.)</b>	<b>58.7, 71.4</b>

The above results are typical averages taken from quality assurance testing. Product technical data are subject to change without notice. \*for further details see separate warranty statement.

Last Update - 2018